

LIMITED LIABILITY COMPANY RN-BUZULUKSKIY GAS PROCESSING PLANT

Legal address of the enterprise: 461040, Orenburg region, Buzuluk city, Technicheskaya str., 10
Telephone: (35342)39-601, fax (35342) 39-602, email: bgpp_priemnaya@rosneft.ru
Production address: Russia, Orenburg region, Grachevsky district, Pokrovka village (Novonikolsky village), Promzempya 101, Pokrovskaya GTU

FAL

QUALITY CERTIFICATE NO. 3657

Hydrocarbon liquefied fuel gas grade propane-butane automobile (PBA) GOST R 52087-2018 EAEU Declaration of Conformity No. RU D-RU.RA01.V.08119/21 is valid until 12.04.2024.

OKPD 2 19.20.31 CUCC FEA 2711129700

Batch No. <u>3657</u>	Date of product manufacture: 29.06.2021
Tank No	Date of sampling: 29.06.2021
Net weight, t	ND of the sampling method GOST 14921-2018
Net volume*, l	Test date: 29.06.2021

Sampling and testing were carried out by the Chemical Laboratory of LLC RN-BGPP, certificate of accreditation No. RA.RU21NV73 dated 05.04.2018

Name of indicator	Testing method	Norn	n no TR	Norm according to GOST	Actual value
1. Octane number, minimum	Appendix B GOST EN 589		39.0	Not standardized	92.3
2. Mass fraction of components, % the amount of methane, ethane and ethylene		Not standardized			1.9
the amount of propane and propylene		Not standardized		58.4	
including propane	GOST 10679	Not standardized 50±10		50±10	58.4
- the amount of butanes and butylenes		Not standardized		39.7	
the amount of unsaturated hydrocarbons, max		6.0		Less than 0.1	
3. Volume fraction of liquid residue at 20°C, %, max	GOST 52087 item 8.2	1.6		Less than 0.1	
4. Saturated vapor pressure is excessive, MPa, at temperature: plus 45°C, max	GOST 28656 item 4.6 2	1.6			1.17
minus 20°C, m <mark>inimum</mark>		0.07		0.10	
minus 30°C, minimum		Not standardized			0.07
5. Mass fraction of hydrogen sulfide and mercaptan sulfur, %, max	GOST 22985	0.01		0.0059	
including hydrogen sulfide,%, max		0.003		Less than 0.0002%	
6. Free water and alkali content	GOST 52087 item 8.2	Absence		Absence	
7. Odor intensity, points, minimum	GOST 22387.5	Not standardized		3	
8. Odor	Appendix B GOST R 52087			haracteristic at a the air of 20% of IP	unpleasant and characteristic at a concentration in the air of 20% of the NIP
9. Density at a temperature of 15°C, kg/m ³	GOST 28656 item 1		Not stan	dardized	529.6

^{*} The net volume of the product is calculated based on the density at 15°C.

The product complies with the requirements of the EAEU TR 036/2016 "Requirements for liquefied petroleum gases for use as fuel" as motor fuel for motor transport.

The product meets the requirements of GOST R 52087 - 2018 item 4.2, table.2 for the PBA grade

The gas is odorized, yes/no - no

The quality certificate is formed on the basis of test report No. <u>5342</u> of <u>29.06.2021</u>

Date of issue of the quality certificate No. 3657 29.06.2021



			Seal:	
Shift Supervisor		Signature	LIMITED LIABILITY COMPANY LLC RN-BUZULUK GAS	A.V. Nikolaev
	·	Signature	PROCESSING PLANT	FULL NAME

The manufacturer guarantees that the product meets the requirements of the standard within 3 months from the date of manufacture, subject to the rules of transportation and storage.

Reprinting and copying of this certificate without the permission of LLC RN-BGPP is prohibited

the end of the quality certificate No. 365